

Liftmoore, Inc.

SERVICE BODY PRODUCT LISTING

Contact Liftmoore for Special Applications
This list is comprised of our Standard Units only.

PUBLIC
Effective July 29, 2018

Index	Page 1
Terms	Page 2
Crane Ready Service Body and Accessories	Page 3
Crane Ready Service Body Upfit for Hydraulic Crane and Hydraulic Outriggers	Page 4
Crane Ready Service Body Upfit for Hydraulic Crane and Hydraulic Outriggers, Painted	Page 5
Accessories - Mounting Kit, Wiring Harnesses, Bulkhead Reservoir	Page 6
Liftmoore Warranty	Page 7

Visit our website at www.liftmoore.com for specifications on the complete Liftmoore line of cranes and products.

Discounts and Terms

Liftmoore warrants its service body products for twelve (12) months from date of shipment as defined in its Limited Warranty and six (6) years for rust through. A copy of the warranty is at the end of this document.

All specifications are subject to correction due to typographical errors.

CRANE READY SERVICE BODY CRANE BODY - ALL ITEMS LOOSE

Item No.	Description
LM-CB-1102	CRANE BODY 40K 84CA X 132OAL 2 BTL COMPMT - D-RING LATCH

SPECIFICATIONS

40,000 ft.-lbs. crane ready service body for 84" CA chassis, 132" long, 94" wide, 44" high, with a 22" compartment depth, 50" load area, and 27" floor line. 63" tall front compartment with holder for 2 bottles

BODY CONSTRUCTION

12 gauge galvaneal front, rear, and bottom compartment panels
12 gauge tread plate compartment tops, load area walls and front bulkhead
Fenders, door facings, and tailgate are 14 gauge A40 galvaneal steel
Holes for recess lights punched high in rear panel and in crane support box with additional support plates
Interior support for underside of boom support mounting

FLOOR

1/8" medium pattern tread plate floor with reinforced understructure
6 Tie-down rings, floor mounted, folding recessed, capacity 2,000 lbs. each

UNDERSTRUCTURE

Front, rear, and rear extension cross members 5" x 3" x 3/16" rectangular tubing
5" high 3/16" formed intermediate cross members
5" high 6.7# structural steel front extension cross members
3 full length formed 12 gauge steel "C" channel longitudinals
1/2" steel flat bar long runners
Automotive grade undercoating

DOORS

Double panel doors with 14 gauge galvaneal steel outer panel and 18 gauge corrugated inner panel
Door design includes a knife edge for continuous positive contact with the door seal
Stainless steel 3 point D-Ring latch assembly
Stainless steel 5/16" diameter rod hinge pins, stainless steel pillow block hinges, self-lubricating plastic bushings
Spring loaded door retainers on vertical doors, chain supports on horizontal doors
Master lock, spring loaded return to the open position

TAILGATE

Slam latch tailgate with 12 gauge tread plate overlay and center release stainless latch

DRAWERS AND SHELVING

Adjustable shelving - 3 vertical compartments and 2 horizontal compartments with 15 dividers, all galvaneal steel
Drawer unit - 31" tall, 34" wide 20" deep - 2 each 3", 6", 9" - Compartment behind driver with dividers. Capacity 250 lbs. each

INCLUDED - SHIPPED LOOSE FOR INSTALLATION AFTER PAINT

LED light kit - tail and clearance lights (shipped loose for installation after paint)
Rubber roll crown fenders (shipped loose for installation after paint)
Door seal, automotive type square bulb EPDM (shipped loose for installation after paint)
Floor drain plugs (shipped loose for installation after paint)

NOT INCLUDED AND REQUIRED

Crane - See Liftmoore Price List for options and additional requirements
Outriggers or jackstands - See Liftmoore Price List for options
Hydraulic reservoir and hoses for hydraulic crane and outriggers
Tailshelf / bumper - See accessories page for Liftmoore options
Boom rest - See Liftmoore Price List for options
Pump and PTO for hydraulic power supply - see chassis manufacturer's and crane's requirements
Wiring adapter specific to chassis manufacturer - see accessories page for options
Mounting kit specific to chassis manufacturer - see accessories page for options
Holes for mounting bolts of crane. Order INST-2002, INST-2003, or INST-2004. Machined at no charge.
Mounting bolts for Liftmoore Model 5000, 2550, 3055, 6036, 3660, or 4064 (PN 28440) - see accessories page for options
Holes and kit for fuel fill and DEF when required
Top coat paint

Body assembled in prime paint
Weight = 3,820 lbs. approximate

**CRANE READY SERVICE BODY
BODY WITH MANUAL OUTRIGGER AND TAILSHELF INSTALLED
BODY SHIPPED IN PRIME PAINT**

Item No. Description
LM-CB-1117 CRANE BODY 40K 84CA X 132OAL
OUTRIG MOCD, TS INSTALLED

SPECIFICATIONS

LM-CB-1102 - See page 3 for details

LM-ACCY-1019 - See accessories page for details

Outrigger - Manual 36" out curbside, 12" streetside manual crankdown jacks

Crankdown Jacks shipped loose - to be welded in at an appropriate height as needed

INCLUDED - SHIPPED LOOSE FOR INSTALLATION AFTER PAINT

LED light kit - tail and clearance lights

Rubber roll crown fenders

Door seal, automotive type square bulb EPDM

Floor drain plugs

NOT INCLUDED AND REQUIRED

Crane - See Liftmoore Price List for options

Mounting bolts for Liftmoore Model 5000, 2550, 3055, 6036, 3660, or 4064 (PN 28440) - see accessories page for options

- Mounting holes for crane machined at no charge

Boom Rest for crane

- A Liftmoore boom rest purchased with the body will be installed at no charge

Wiring adapter specific to chassis manufacturer - see accessories page for options

Mounting kit specific to chassis manufacturer - see accessories page for options

Holes and kit for fuel fill and DEF when required

Top coat paint

Any provision for hydraulics

Auxiliary batteries when required

Body assembled in prime paint

Weight = 4,200 lbs. approximate

OPTIONS

INST-2005 PAINT & INSTALL ON CRANE BODY
INC. LM-CB-1113 & LM-CB-1114

Top coat paint, Liftmoore white on the body, outriggers, tailshelf, and inside compartments

Install Rear mount LED light kit - tail and clearance lights

Install Rubber roll crown fenders

Install Door gasket

Install Floor drain plugs

CRANE READY SERVICE BODY
BODY WITH HYDRAULIC OUTRIGGER, TAILSHELF, AND HYDRAULIC KIT INSTALLED
BODY SHIPPED IN PRIME PAINT

Item No.	Description
LM-CB-1105	CRANE BODY 40K 84CA X 132OAL WITH HYDRAULIC KIT INSTALLED

SPECIFICATIONS

LM-CB-1102 - See page 3 for details

LM-ACCY-1019 - See accessories page for details

Outrigger - Hydraulic 42" out & down curbside, hydraulic down only outrigger streetside, cylinders installed

Valves mounted

 Diverter for outrigger and crane

 Lever controls for outrigger

 Flow control for outrigger

Boom rest installed for Model 2550, 3055, 3660, or 4064

Hydraulic installation kit

 Reservoir, hydraulic oil 25 gallon capacity mounted in the cargo area at front of body

 Filter, oil return line - installed at reservoir

 Cutoff valve, inline

 Hose from outrigger to crane compartment, installed

 Hose from crane compartment to front of body, installed

Mounting holes for crane

INCLUDED - SHIPPED LOOSE FOR INSTALLATION AFTER PAINT

 LED light kit - tail and clearance lights

 Rubber roll crown fenders

 Door seal, automotive type square bulb EPDM

 Floor drain plugs

NOT INCLUDED AND REQUIRED

 Crane - See Liftmoore Price List for options

 Pump and PTO for hydraulic power supply - see chassis manufacturer's and crane's requirements

 Hose from reservoir to pump

 Hose from pump to front of body

 Wiring adapter specific to chassis manufacturer - see accessories page for options

 Mounting kit specific to chassis manufacturer - see accessories page for options

 Mounting bolts for Liftmoore Model 5000, 2550, 3055, 6036, 3660, or 4064 (PN 28440) - see accessories page for options

 Holes and kit for fuel fill and DEF when required

 Top coat paint

Body assembled in prime paint

Weight = 4,680 lbs. approximate

**CRANE READY SERVICE BODY
BODY WITH HYDRAULIC OUTRIGGER, TAILSHELF, AND HYDRAULIC KIT INSTALLED
TOP COAT PAINT (LIFTMOORE WHITE)**

**LM-CB-1106 CRANE BODY 40K 84CA X 132OAL
LM-CB-1105 PAINTED FINAL INST.**

SPECIFICATIONS

LM-CB-1105 - See page 4 for details

Top coat paint, Liftmoore white on the body, outriggers, tailshelf, and inside compartments

Install Rear mount LED light kit - tail and clearance lights

Install Rubber roll crown fenders

Install Door gasket

Install Floor drain plugs

NOT INCLUDED AND REQUIRED

Crane - See Liftmoore Price List for options

Pump and PTO for hydraulic power supply - see chassis manufacturer's and crane's requirements

Hose from reservoir to pump

Hose from pump to front of body

Wiring adapter specific to chassis manufacturer - see accessories page for options

Mounting kit specific to chassis manufacturer - see accessories page for options

Mounting bolts for Liftmoore Model 5000, 2550, 3055, 6036, 3660, or 4064 (PN 28440) - see accessories page for options

Holes and kit for fuel fill and DEF when required

Weight = 4,680 lbs. approximate

SERVICE BODY ACCESSORIES

Item No. Description
LM-ACCY-1019 TAILSHELF, 8" STEP PINTLE RCES

SPECIFICATIONS

Tailshelf with compartments and 8" deep tread plate step with ball hook recess, modified to mount and allow tailgate to open and with modified mount plates. Includes D-Ring latches to match those on body.
 Weight = 360 lbs.

INCLUDED - SHIPPED LOOSE FOR INSTALLATION

Bumper arms

MOUNTING KITS AND TAIL LIGHT CONNECTIONS

LM-ACCY-1018 SERVICE BODY MOUNTING KIT 40K
 FORD F-550/ RAM 5500 84CA-132"

LM-ACCY-1033 SERVICE BODY MOUNTING KIT 40K
 RAM 5500 84CA-132"

LM-ACCY-1021 WIRING ADAPTER KIT FORD SD
 USE W/ LM-ACCY-1022

LM-ACCY-1022 WIRING ADAPTER KIT FORD SD RK
 USE W/ LM-ACCY-1021

LM-ACCY-1031 WIRING ADAPTER KIT DODGE SD RK
 USE W/ LM-ACCY-1022

28440 KIT, MOUNTING CRANE 0.875" BOLT
 5000/2550/3055/6036/3660/4064

HOLES DRILLED FOR CRANE MOUNTING

INST-2002 DRILL 12.0" BOLT PATTERN FOR 0.50" BOLTS
 Mounting pattern for 2000, 208, 2700, 3200, 3612, 1032, LA10K

INST-2003 DRILL 12.0" BOLT PATTERN FOR 0.75" BOLTS
 Mounting pattern for 4000, 1640

INST-2004 DRILL 14.75" BOLT PATTERN FOR 0.875" BOLTS
 Mounting pattern for 5000, 2550, 3055, 6036, 3660, 4064

LIFTMOORE LIMITED WARRANTY

Crane Bodies

Liftmoore, Inc. warrants each Liftmoore, Inc. service body to be free from defects in materials and workmanship for twelve (12) months from the date of delivery to the original customer. Additionally, Liftmoore, Inc. provides a rust through warranty of six (6) years. Exclusions to this warranty include, but are not limited to: when corrosive materials have been transported; when liner coating is used; fatigue fractures due to misuse, accident, improper installation; damage from road conditions; top coat if not applied by Liftmoore, Inc.; modifications not performed by Liftmoore, Inc.; improper or lack of maintenance; installation other than by Liftmoore, Inc. or an authorized distributor. Under the terms of this warranty Liftmoore, Inc. will repair or replace, at its sole discretion, any equipment or part that is returned F.O.B. to Liftmoore, Inc.'s plant at 7810 Pinemont Drive, Houston, Texas 77040, or to one of its authorized dealers, and is found by Liftmoore, Inc. or its authorized dealer to have been defective at the time of original delivery.

The foregoing warranty is the exclusive warranty made by Liftmoore, Inc. with respect to its service bodies and is in lieu of all other warranties. ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS OF ANY service body FOR A PARTICULAR PURPOSE OR OPERATION, ARE HERBY EXPRESSLY DISCLAIMED.

The foregoing warranty applies only to Liftmoore, Inc. service bodies under normal use and service and does not apply in the event of damage caused by repair or alteration or damage during shipment, accident, negligence, overloading, or misuse, including operator's failure to follow any of the instructions issued with the service body.

This warranty is limited to the original purchaser and is not assignable. In order to submit a claim, the original purchaser must provide a copy of the original invoice for the service body in question within twelve (12) months following the delivery date and within 30 days from the date of repair or within six (6) years following the delivery date for rust through claims.

The warranty applies only when the Liftmoore, Inc. service body is used for commercial purposes and does not cover any purchase for use for personal, family or household purposes.

LIMITATION OF LIABILITY: Liftmoore, Inc.'s liability for any losses or damages resulting from any cause whatsoever, including Liftmoore, Inc.'s NEGLIGENCE or from a defective service body irrespective of whether such defects are discoverable or latent, shall in no event exceed the purchase price of the service body to which losses or damages are claimed, or at the election of Liftmoore, Inc., the repair or replacement of the defective service body.

In no event shall Liftmoore, Inc. be liable for any special, incidental, or consequential damages, including commercial losses or costs of any kind sustained by purchaser or any other person or for any damages for which purchaser may be liable to other persons by reason of any defect in any Liftmoore, Inc. service body or any part thereof.

Liftmoore, Inc. reserves the right to make changes in design or construction of its service bodies at any time without obligating itself to make such changes on service bodies previously manufactured.

No agent, employee, or representative of Liftmoore, Inc. has authority to amend or modify the foregoing warranty or to bind Liftmoore, Inc. by any other warranty, guaranty, or assumption of liability.

In the event any provision of this warranty is for any reason held ineffective, the remaining provisions shall remain in full force and effect.

Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other legal rights that vary from state to state.

